



SCALE:

0 10 FT.

SCALE:

MARK	VENDOR / MOD. NO.	DESCRIPTION	NOTES
WC-1	TOTO / MOD. CST454CEFL	WATER CLOSET W/ LEFT HAND LEVER AND OPEN FRONT COMMERCIAL SEAT - 19" AFF. TOP OF SEAT	1.
LAV-1	AMERICAN STANDARD / MOD. 012A02A	RESTROOM LAVATORY	2.
KS-1	ELKAY / MOD. S-4819-L (LEFT HAND)	SINK: SINGLE BOWL W/ SINGLE DRAINBOARD - FITS 48" BASE CABINET	3.
DS-1	CECO / MOD. 845	DEEP SINK - CAST IRON PORCELAIN ENAMELED	5.
WH-1	CHROMAMITE MOD.# SR-40	ELECTRIC WATER HEATER (POINT-OF-USE) - 2P-50 AMP - 9600 WATTS	6.
WH-2	CHROMAMITE MOD.# SR-40	ELECTRIC WATER HEATER (POINT-OF-USE) - 2P-50 AMP - 9600 WATTS	7.
EM-S&EW	HAWES / MOD. 8996WNC	EMERGENCY: SHOWER AND EYE WASH	
HD	WOODFORD / 24 - INTERIOR	INTERIOR HOSE BIBB	
FP-YH	WOODFORD / U200 - EXTERIOR	EXTERIOR "FREEZELESS" - YARD HYDRANT	
WS	KINETICO / MOD. CP 216	WATER SOFTENER	
P.T.	WELL-RITE / MOD.#WR-100	PRESSURE TANK - WELL DIAPHRAGM	4.
FD.	JR SMITH / MOD.#J04S	FLOOR DRAIN WITH CLEAN OUT	

1. INSTALL ELONGATED OPEN FRONT TOILET SEAT: TOTO MOD. SC534 OR APPROVED EQUAL.
2. INSTALL FAUCETS & WRIST BLADE HANDLES AMERICAN STANDARD MOD. #5501170 OR APPROVED EQUAL.
3. INSTALL FAUCETS WITH 5" WRIST BLADE HANDLES ELKAY MOD. LK-232-S-BH-5 WITH H&C WATER HOLES @ 8" ON CENTER
4. CONNECT WITH ONE INCH (1") BLUE POLY PIPE.
5. SUPPLY DEEP SINK W/ WRIST BLADE HANDLES AMERICAN STANDARD MOD. 8345101 OR APPROVED EQUAL.
6. RESTROOM WATER HEATER TEMPERATURE SHALL BE PRE-SET TO 110 F. WITH MIN. #8 WIRE.
7. UTILITY/SHOP SINK WATER HEATER TEMPERATURE SHALL BE PRE-SET TO 120 F. WITH MIN. #8 WIRE.

SCALE: N.T.S.

