

**PROFILE WALL POLYVINYL CHLORIDE PIPE
HEIGHT OF COVER LIMITS (m)**

DIAMETER (mm)	MINIMUM (m)	MAXIMUM (m)
450	0.61	10.4
525	0.61	10.1
600	0.61	9.4
675	0.61	9.1
750	0.61	8.8
900	0.61	8.2


**SMOOTH WALL POLYVINYL CHLORIDE PIPE
HEIGHT OF COVER LIMITS (m)**

PAY ITEM DIAMETER (mm)	NOMINAL DIAMETER (mm)	MINIMUM (m)	MAXIMUM (m)
300	300	0.61	19.5
375	375	0.61	19.5
450	475	0.61	18.6
525	560	0.61	18.6
600	630	0.61	18.6
675	710	0.61	18.6

NOTE:

- The tabulated cover depths shall be measured from the bottom of the concrete or bituminous pavement to the top of the pipe.
- The pay item diameter reflects the minimum required inside diameter.

All dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION	
PIPE HEIGHT OF COVER LIMITS	
JANUARY 1998	
STANDARD DRAWING NO. 715-PHCL-19	
	/s/ Anthony L. Uremovich 1-02-98 DESIGN STANDARDS ENGINEER DATE
DESIGN STANDARDS ENGINEER	/s/ Donald W. Lucas 1-02-98 CHIEF HIGHWAY ENGINEER DATE

Source Sheet: NONE