


FRONT VIEW



SIDE VIEW

TYPICAL SIGN STANDARD
& ROAD CLOSURE SIGN ASSEMBLY

GENERAL NOTES

- ① The minimum vertical clearance for construction signs shall be as follows:
 - a) 2.1 m between the top of the curb and the bottom of the sign on-curbed roadway sections.
 - b) 2.1 m between the edge of pavement and the bottom of the sign on non-curbed roadway sections.
 - c) An advisory speed plate, required to be placed with another construction sign, shall be mounted on the post closest to the roadway at a minimum clearance of 1.8 m above the edge of pavement. The bottom of the construction warning sign shall not be lower than the top of the advisory speed plate.
2. See Standard Drawing 801-TCSN-11 for additional notes.

All dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION	
TYPICAL SIGN STANDARD	
SEPTEMBER 1997	
STANDARD DRAWING NO. 801-TCDV-05	
	<i>/s/ Anthony L. Uremovich</i> 9-01-97 DESIGN STANDARDS ENGINEER DATE
	<i>/s/ Donald W. Lucas</i> 9-01-97 CHIEF HIGHWAY ENGINEER DATE

Source Sheet: DET 2A