


GENERAL NOTES

1. The pavement section for traffic volumes or percent trucks exceeding the values shown in (S) in the Legend shall be as shown elsewhere in the plans.
2. The surface course shall be placed when the runaround is in service between December 1 and the following April 1.
3. A temporary bridge or temporary pipe shall be used as specified. A 8.5 m clear roadway width shall be provided on a temporary bridge.
- ④ The connection of the temporary runaround to the existing pavement shall be outside the limits of the approach pavement removal.
- ⑤ Temporary pavement markings will be required as shown. The contractor shall have the option of using temporary tape or paint for all temporary pavement markings except where otherwise specified.
- ⑥ Delineators type D-2 (white) shall be placed at 9 m maximum spacing on both sides throughout the length of the temporary runaround, including across the temporary structure. If a temporary bridge is used, type 3 object markers shall be placed at all four corners in accordance with the MUTCD.
- ⑦ Spacing of drums at this location shall be 6 m.
- ⑧ If the runaround posted speed limit is greater than 30 mph the reverse curve sign (XW1-4-A, 900 x 900) shall be used at this location. If the runaround posted advisory speed limit is 30 mph or less, the reverse turn sign (XW1-3-A, 900 x 900) shall be used.

LEGEND

- ⊖ Delineator type D-2 (white)
- ⑧ Pavement section for ADT < 4500 and maximum of 10% trucks shall be:
 75 kg/m² HMA Surface 9.5 mm
 345 kg/m² HMA intermediate 19.0 mm
 150 mm compacted aggregate base, size No. 53
 (See General Notes 1 and 2.)

All dimensions are in mm unless otherwise specified.

| | |
|---|--|
| INDIANA DEPARTMENT OF TRANSPORTATION | |
| TEMPORARY RUNAROUND | |
| GENERAL NOTES | |
| JANUARY 1999 | |
| STANDARD DRAWING NO. 713-TCTR-04 | |
|  | /s/ Anthony L. Uremovich 1-04-99 DESIGN STANDARDS ENGINEER DATE |
| | /s/ Donald W. Lucas 1-04-99 CHIEF HIGHWAY ENGINEER DATE |

Source Sheet: Det.1-D