


**RUB-RAIL RELOCATION DETAIL**

**GENERAL NOTES**

**GUARDRAIL TRANSITION TYPE VH AT 12'-6" POST SPACING**

1. The details on this sheet are for the height adjustment of existing rub-rail type guardrail.
2. Guardrail transition type VH at 12'-6" post spacing shall be used where new W-beam guardrail is being attached to existing rub-rail type W-beam guardrail at 12'-6" post spacing. This transition shall also be used where a new lower height guardrail end treatment is being attached to existing 12'-6" spaced rub-rail type guardrail.
3. If rub-rail is not spliced at post, the channel shall be cut and repositioned behind the flange.
4. If rub-rail is spliced at post, the splice material shall be removed and the channel shall be repositioned behind the flange.

INDIANA DEPARTMENT OF TRANSPORTATION	
<b>GUARDRAIL TRANSITION TYPE VH</b>	
APRIL 1995	
STANDARD DRAWING NO. <b>E 601-TTVH-02</b>	
	DETAILS PLACED IN THIS FORMAT 11-15-99 /s/ Anthony L. Uremovich 11-15-99 <small>DESIGN STANDARDS ENGINEER DATE</small>
<small>DESIGN STANDARDS ENGINEER</small>	/s/ Firooz Zandi 11-15-99 <small>CHIEF HIGHWAY ENGINEER DATE</small> <small>ORIGINALLY APPROVED 4-03-95</small>