GENERAL NOTES

These notes are for Standard Drawings 610-PRAP-10 and 610-PRAP-12.

- 1. Standard Drawings 610-PRAP-10 and -12 are for intersection control angle 70° to 110°. If intersection control angle is less than 70° or greater than 110° a special design will be required.
- (2) See table on Standard Drawing 610-PRAP-04 for embankment slopes to be built on either side of the approach
- 3. Cross culverts under the public road approach which cannot be located outside the mainline clear zone will require an appropriate end section at each end.
- If the existing pavement is asphalt the transition area shall be the same section as the approach and will be included in the pay limits for HMA for Approaches.

5	The cross hatched	shoulder shoulder	area indicates the limit
	where the shoulder	r is the same as the	approach pavement.

- 6. If the approach is to be constructed of PCCP, the details shall be as shown elsewhere in the plans for pavement thickness, joint type, and location.
- 7. If the Class V or above truck count for the public road approach is greater than 50 per day, the required pavement section shall be as provided elsewhere in the plans
- The pavement section for the turn lane shall be as shown elsewhere in the plans.

Design speed	TABLE A										
	MINIMUM LENGTH OF TURNING LANES (excluding taper), ft.										
	Downgrade slope in %				Upgrade slope in %						
km / h	6 to 5	4.99 to 4	3.99 to 3	2.99 to 2.01	2 to 0	0 to 2	2.01 to 2.99	3 to 3.99	4 to 4.99	5 to 6	
60	130	125	115	105	95	95	90	85	80	75	
80	185	175	165	150	135	135	130	120	115	110	
100	225	215	200	185	165	165	160	150	140	135	
110	250	240	225	205	185	185	180	170	160	150	

All Dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION

PUBLIC ROAD APPROACH TYPE D **GENERAL NOTES AND TABLE A**

SEPTEMBER 2007

STANDARD DRAWING NO. 610-PRAP-11



/s/Richard L. VanCleave 09/04/07 **DESIGN STANDARDS ENGINEER** DATE

/s/ Mark A. Miller CHIEF HIGHWAY ENGINEER 09/04/07 DATE