

**TYPICAL PARTIAL CONCRETE BRIDGE RAILING  
TYPE TF-2 ELEVATION VIEW**

(WITHOUT INLET PLACEMENT SHOWN;  
WITH INLET PLACEMENT SIMILAR)

**NOTES**

1 SPACING OF JOINTS IN TUBE STEEL  
MAXIMUM: 12000 MINIMUM: 6000

2 POST SPACING MAXIMUM: 2250 MINIMUM: 1200

3 DISTANCE FROM CENTERLINE OF SPLICING  
TO CENTERLINE OF RAILING POST: MAXIMUM: 750  
MINIMUM: 450

④ Ø RAILING POST TO EDGE OF OPEN JOINT IN RAILING.

5. Pay limits for concrete bridge railing Type TF-2 to  
end of railing.


All dimensions are in mm unless otherwise specified

INDIANA DEPARTMENT OF TRANSPORTATION

**CONCRETE BRIDGE RAILING  
TYPE TF-2**

SEPTEMBER 2005

STANDARD DRAWING NO. 706-BRTF-07



/s/ Richard L. VanCleave 9-01-05  
DESIGN STANDARDS ENGINEER DATE

/s/ Richard K. Smutzer 9-01-05  
CHIEF HIGHWAY ENGINEER DATE

DESIGN STANDARDS ENGINEER