

**125 mm x 25 mm CORRUGATED STEEL PIPE (LOCK SEAM)
HEIGHT OF COVER LIMITS (m)**

	AREA (m ²)	DIAMETER (mm)	THICKNESS (mm)									
			1.63		2.01		2.77		3.51		4.27	
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
	0.64	900	X	X	0.30	27.4	0.30	30.5	X	X	X	X
	0.87	1050	X	X	0.30	23.5	0.30	30.5	X	X	X	X
	1.13	1200	0.30	16.5	0.30	20.7	0.30	29.0	0.30	30.5	X	X
	1.43	1350	0.30	14.8	0.30	18.5	0.30	25.9	0.30	30.5	X	X
	1.77	1500	0.30	13.1	0.30	16.5	0.30	23.2	0.30	29.9	X	X
	2.14	1650	0.30	11.9	0.30	14.9	0.30	21.0	0.30	27.1	X	X
	2.54	1800	0.30	11.0	0.30	13.7	0.30	19.2	0.30	24.7	0.30	30.5
	2.99	1950	0.30	10.2	0.30	12.8	0.30	17.9	0.30	23.0	0.30	28.2
	3.46	2100	0.30	9.4	0.30	11.6	0.30	16.5	0.30	21.3	0.30	25.9
	3.98	2250	0.30	8.8	0.30	11.0	0.30	15.2	0.30	19.8	0.30	24.4
	4.52	2400	X	X	0.30	10.4	0.30	14.3	0.30	18.6	0.30	22.9
	5.11	2550	X	X	0.32	9.8	0.32	13.7	0.32	17.6	0.32	21.5
	5.73	2700	X	X	X	X	0.34	12.8	0.34	16.5	0.34	20.1
	6.38	2850	X	X	X	X	0.36	12.2	0.36	15.8	0.36	19.3
	7.07	3000	X	X	X	X	0.38	11.6	0.38	14.9	0.38	18.3
	7.79	3150	X	X	X	X	X	X	0.39	14.3	0.39	17.4
	8.55	3300	X	X	X	X	X	X	0.41	13.4	0.41	16.5
	9.35	3450	X	X	X	X	X	X	0.43	13.0	0.43	15.9
	10.18	3600	X	X	X	X	X	X	X	X	0.45	15.2

NOTE:

1. The tabulated cover depths shall be measured from the bottom of the bituminous or concrete pavement to the top of the pipe.

All dimensions are in mm unless otherwise specified.

INDIANA DEPARTMENT OF TRANSPORTATION
PIPE HEIGHT OF COVER LIMITS
 JANUARY 1998
 STANDARD DRAWING NO. 715-PHCL-15

/s/ Anthony L. Uremovich <small>DESIGN STANDARDS ENGINEER</small>	1-02-98 <small>DATE</small>
/s/ Donald W. Lucas <small>CHIEF HIGHWAY ENGINEER</small>	1-02-98 <small>DATE</small>

Source Sheet: NONE